



M12DF

12D Drill With
Coolant Holes

Stock	Order No	Code	d1h7	d2h6	l1	l2	l3
	74100	M12DF.2.0300.0920.A0135.0480.0000.0540.00.S06A2B03.01	3	6	92	48	54
	74102	M12DF.2.0310.0920.A0135.0480.0000.0540.00.S06A2B03.01	3,1	6	92	48	54
	74104	M12DF.2.0320.0920.A0135.0480.0000.0540.00.S06A2B03.01	3,2	6	92	48	54
	74106	M12DF.2.0330.0920.A0135.0480.0000.0540.00.S06A2B03.01	3,3	6	92	48	54
	74108	M12DF.2.0340.0920.A0135.0480.0000.0540.00.S06A2B03.01	3,4	6	92	48	54
	74110	M12DF.2.0350.0920.A0135.0480.0000.0540.00.S06A2B03.01	3,5	6	92	48	54
	74112	M12DF.2.0360.0920.A0135.0480.0000.0540.00.S06A2B03.01	3,6	6	92	48	54
	74114	M12DF.2.0370.0920.A0135.0480.0000.0540.00.S06A2B03.01	3,7	6	92	48	54
	74116	M12DF.2.0380.1020.A0135.0580.0000.0640.00.S06B2A05.01	3,8	6	102	58	64
	74118	M12DF.2.0390.1020.A0135.0580.0000.0640.00.S06B2A05.01	3,9	6	102	58	64
	74120	M12DF.2.0400.1020.A0140.0580.0000.0640.00.S06C2B02.01	4	6	102	58	64
	74122	M12DF.2.0410.1020.A0140.0580.0000.0640.00.S06C2B02.01	4,1	6	102	58	64
	74124	M12DF.2.0420.1020.A0140.0580.0000.0640.00.S06C2B02.01	4,2	6	102	58	64
	74126	M12DF.2.0430.1020.A0140.0580.0000.0640.00.S06C2B02.01	4,3	6	102	58	64
	74128	M12DF.2.0440.1020.A0140.0580.0000.0640.00.S06C2B02.01	4,4	6	102	58	64
	74130	M12DF.2.0450.1020.A0140.0580.0000.0640.00.S06C2B02.01	4,5	6	102	58	64
	74132	M12DF.2.0550.1160.A0135.0700.0000.0780.00.S06B2B03.01	4,6	6	102	58	64
	74134	M12DF.2.0470.1020.A0140.0580.0000.0640.00.S06C2B02.01	4,7	6	102	58	64
	74136	M12DF.2.0480.1160.A0135.0700.0000.0780.00.S06B2B03.01	4,8	6	116	70	78
	74138	M12DF.2.0490.1160.A0135.0700.0000.0780.00.S06B2B03.01	4,9	6	116	70	78
	74140	M12DF.2.0500.1160.A0135.0700.0000.0780.00.S06C2B02.01	5	6	116	70	78
	74142	M12DF.2.0530.1260.A0140.0750.0000.0880.00.S06C2B02.01	5,3	6	126	75	88
	74144	M12DF.2.0550.1160.A0135.0700.0000.0780.00.S06B2B03.01	5,5	6	116	70	78
	74146	M12DF.2.0560.1220.A0140.0840.0000.0750.00.S06C2B02.01	5,6	6	122	84	75
	74148	M12DF.2.0580.1160.A0135.0700.0000.0780.00.S06B2B03.01	5,8	6	116	70	78
	74150	M12DF.2.0600.1160.A0135.0700.0000.0780.00.S06C2B02.01	6	6	116	70	78
	74152	M12DF.2.0630.1460.A0135.0940.0000.1080.00.S08B2B02.01	6,3	8	146	94	108
	74154	M12DF.2.0650.1460.A0135.0940.0000.1080.00.S08B2B02.01	6,5	8	146	94	108
	74156	M12DF.2.0660.1460.A0135.0940.0000.1080.00.S08B2B02.01	6,6	8	146	94	108
	74158	M12DF.2.0680.1460.A0135.0940.0000.1080.00.S08B2B02.01	6,8	8	146	94	108
	74160	M12DF.2.0700.1460.A0135.0940.0000.1080.00.S08B2B02.01	7	8	146	94	108
	74162	M12DF.2.0750.1460.A0135.0940.0000.1080.00.S08B2B02.01	7,5	8	146	94	108
	74164	M12DF.2.0780.1460.A0135.0940.0000.1080.00.S08B2B02.01	7,8	8	146	94	108
	74166	M12DF.2.0800.1460.A0135.0940.0000.1080.00.S08B2B02.01	8	8	146	94	108
	74168	M12DF.2.0820.1620.A0135.1100.0000.1200.00.S10C2B02.01	8,2	10	162	110	120
	74170	M12DF.2.0850.1620.A0135.1100.0000.1200.00.S10C2B02.01	8,5	10	162	110	120
	74172	M12DF.2.0900.1620.A0135.1100.0000.1200.00.S10C2B02.01	9	10	162	110	120
	74174	M12DF.2.0950.1620.A0135.1100.0000.1200.00.S10B2B03.01	9,5	10	162	110	120
	74176	M12DF.2.0980.1620.A0135.1100.0000.1200.00.S10B2B03.01	9,8	10	162	110	120
	74178	M12DF.2.1000.1620.A0135.1100.0000.1200.00.S10B2B03.01	10	10	162	110	120
	74180	M12DF.2.1050.2040.A0135.1420.0000.1560.00.S12B2B03.01	10,5	12	204	142	156
	74182	M12DF.2.1100.2040.A0135.1420.0000.1560.00.S12B2B03.01	11	12	204	142	156
	74184	M12DF.2.1150.2040.A0135.1420.0000.1560.00.S12B2B03.01	11,5	12	204	142	156
	74186	M12DF.2.1200.2040.A0135.1420.0000.1560.00.S12B2B03.01	12	12	204	142	156
	74188	M12DF.2.1300.2300.A0135.1660.0000.1820.00.S14B2B03.01	13	14	230	166	182
	74190	M12DF.2.1400.2300.A0135.1660.0000.1820.00.S14B2B03.01	14	14	230	166	182
	74192	M12DF.2.1500.2600.A0135.1920.0000.2080.00.S16B2B02.01	15	16	260	192	208
	74194	M12DF.2.1600.2600.A0135.1920.0000.2080.00.S16B2B02.01	16	16	260	192	208
	74196	M12DF.2.1800.2850.A0135.2160.0000.2340.00.S16B2B02.01	18	18	285	216	234

Cutting Parameters Vc(m/min)

Non-Alloy Steel	100	●
Steel	80	●
Tempered Steel	70	●
Cold-Work Tool Steel	40	○
Hot-Work Tool Steel	40	○
AISI 304 - 416 - 420	35	○
AISI 316 - 440	35	○
17-4 PH 15-5 PH	30	○
Chrome-Cobalt Alloy	30	○
Duplex F51	25	○
Super Duplex F55	25	○
Grey Cast Iron	70	●
Alloy Cast Iron	60	●
Precision Cast	50	●

Feed Per Revolution (mm/rev)

Ø	
3-5	0,05-0,19
5-8	0,08-0,25
8-12	0,1-0,32
12-16	0,12-0,38
16-18	0,13-0,42

α
135°

+TiAlN

FORM
HA DIN
6535

● Recommended ○ Acceptable ○ Not Recommended

*Marked products are available
from stock to deliver fast.